


Product Details

Unique jaw locking control Unique cutter design



Larger jaw opening design



Adaptive joint design



Integral anvil design



Single-handed, controllable cutter retracting Ergonomic design




Product Features

1. Unique cascaded integral anvil effectively disperses force pressed on tissue to ensure good staple molding and hemostasis;
2. Adaptive joint design permits free rotation within 45 degrees, which is convenient for tissue separation operation within a small space;
3. Larger jaw opening design, with 22mm at distal end and 8mm at proximal end, is more convenient for operation on tissues and instrument placement;
4. Unique jaw locking control facilitates opening and closing of the jaws, which simplifies instrument operation and prevents erroneous firing, so that operation safety is ensured;
5. Unique cutter design applies double press on tissue to ensure consistency of staple height, reducing the possibility of bleeding;
6. 3 rows of staples on each side of cartridge and longer inner stapling string design ensure tight suture and increase surgical safety;
7. Double safety lock design (No-Load and Fired) prevents misuse;
8. A variety of choices for cartridge colors meet the needs for different surgical operations and reduce cost;
9. Single-handed operation and ergonomic design simplify instrument handling and improve operation comfort.
10. The design of 3 rows of staples on each side of cartridge increases surgical safety;



Applications

Suitable for reconstruction of digestive tract in minimally invasive surgery, anastomotic stoma construction in tissue resection and closure of stump or incision.

Cascade cartridge surface



A variety of choices for cartridge colors



3 rows of staples on each side of cartridge, longer inner stapling string design

Specification

P/N	SHAFT LENGTH(mm)	SUTURE LENGTH(mm)	STAPLE HEIGHT (mm)
YJHB-30S	220	30	0.75-2.2
YJHB-30M	280	30	0.75-2.2
YJHB-30L	380	30	0.75-2.2
YJHB-45S	220	45	0.75-2.2
YJHB-45M	280	45	0.75-2.2
YJHB-45L	380	45	0.75-2.2
YJHB-60S	220	60	0.75-2.2
YJHB-60M	280	60	0.75-2.2
YJHB-60L	380	60	0.75-2.2

RELOAD NO.	COLOR	STAPLE HEIGHT (mm)	RELOAD NO.	COLOR	STAPLE HEIGHT (mm)
YJZ-30M	●	0.75	YJZ-30D	●	1.75
YJZ-30W	●	1.0	YJZ-30G	●	2.0
YJZ-30B	●	1.5	YJZ-30T	●	2.2
YJZ-45M	●	0.75	YJZ-45D	●	1.75
YJZ-45W	●	1.0	YJZ-45G	●	2.0
YJZ-45B	●	1.5	YJZ-45T	●	2.2
YJZ-60M	●	0.75	YJZ-60D	●	1.75
YJZ-60W	●	1.0	YJZ-60G	●	2.0
YJZ-60B	●	1.5	YJZ-60T	●	2.2